

Favourite will be double favourite from now



Extra pin in 3 point linkage for lower link mounting
To reduce lipping on soft soils.



Improved brake pedal position and additional foot block Provide rest to work longer



Improved reverse speed
Eliminates frequent gear changes.



32" (813mm) track width, 28" (711mm) track optional width

Gives better suitability for farming.



Better fender design

Improved seat pan width
To provide comfort



Now also available with OIB



Aesthetic and new look

Engine

Engine Power kW (HP) 11.12 (15)

Cooling Water Cooled

Fuel Tank Capacity 19

(litres)

Transmission

No. of gears 6 forward, 3 reverse

Maximum speed (km/h)

Break Dry Disc break / OIB

25

Hydraulics

Type Live, ADDC

Lift capacity at hitch point (kg) 778

Lower Link Compatibility with CAT 1N

Tractor Description

Tyre - Front 3.20 x 14.8 (PR)

Tyre - Rear 8.00 x 18.6 (PR)

Turning radius (m) 2.4



🏗 Toll Free No: 1800 425 6576 | www.mahindratractor.com 🜃 facebook.com/MahindraTractorsIndia

💟 twitter.com/TractorMahindra 🍽 📠 youtube.com/MahindraTractorsofficial 🏮 www.instagram.com/mahindratractorsofficial