

Features	mahindra 585DI	mahindra 575DI	mahindra 575DI Lux	mahindra 475DI
<b>Engine</b>				
Engine (CC)	2979	2979	2979	2731
No. of Cylinders	4	4	4	4
PTD power (HP/kW)	44.9/36.8	41.8/31.1	40/29.8	37.4/27.8
Max Torque (Nm)	215	207	201	194
Backup Torque (%)(O)	29.80%	27.10%	32.30%	30.10%
PTD SFC (gm/hp)	190	185	185	181.9
Engine Rated RPM	2100+ (50)	2000+ (50)	2000+ (50)	2000+ (50)
Fuel Tank Capacity (litres)	50	50	48	48
Cooling System	Water Cooled / Thermostat	Water Cooled / Thermostat	Water Cooled / Thermostat	Water Cooled / Thermostat
<b>Transmission</b>				
Type of Transmission	PCM (CS), FCM (SS), SLIPTO	PCM (CS), FCM (SS), SLIPTO	PCM (CS), FCM (SS), SLIPTO	PCM (CS), FCM (SS), SLIPTO
Air Cleaner	Wet	Wet	Wet	Wet
Operating Speeds	8 F X 2 R, 8 F X 8 R (F/R Shuttle)	8 F X 2 R, 8 F X 8 R (F/R Shuttle)	8 F X 2 R	8 F X 2 R
Brake Type	OIB	OIB	OIB	OIB
Clutch Type	Single, Dual & SLIPTO	Single, Dual & SLIPTO	Single, Dual & SLIPTO	Single, Dual & SLIPTO
PTD Speeds	540, 540 & 540E, 540 & Reverse, 540 & 1500	540, 540 & 540E, 540 & Reverse, 540 & 1500	540, 540 & 540E, 540 & Reverse	540, 540 & 540E, 540 & Reverse
<b>Hydraulics</b>				
Hydraulic Lift Capacity at Hitch (Kgs)	2000	1700/2000	1700/2000	1700/2000
Hydraulic Pump Flow (Lpm)	30	28	28	28
<b>Others</b>				
Tyre Size Front	190.50 mm x 406.40 mm (7.5 x 16)	152.40 mm x 406.40 mm (6.0 x 16) 190.50 mm x 406.40 mm (7.5 x 16)	152.40 mm x 406.40 mm (6.0 x 16) 190.50 mm x 406.40 mm (7.5 x 16)	152.40 mm x 406.40 mm (6.0 x 16)
Tyre Size Rear	378.46 mm x 711.20 mm (14.9 x 28)	345.40 mm x 711.20 mm (13.6 x 28) 378.46 mm x 711.20 mm (14.9 x 28) (opt)	345.40 mm x 711.20 mm (13.6 x 28) 378.46 mm x 711.20 mm (14.9 x 28) (opt)	345.40 mm x 711.20 mm (13.6 x 28)
Seat	Delux	Delux	Delux	Delux
Digital Cluster & Speed Indication	Yes	Yes	Yes	Yes
Headlamp Type	Trapezoidal lamp with 75 Lux, 60 55 W	Trapezoidal lamp with 75 Lux, 60 55 W	Trapezoidal lamp with 75 Lux, 60 55 W	Trapezoidal lamp with 75 Lux, 60 55 W
SLIPTO Variant	✓	✓	✓	✓
F/R Shuttle Variant	✓	✓	—	—
<b>Service</b>				
Service Interval Engine	1 <sup>st</sup> at 100 hrs & then every 400 hrs	1 <sup>st</sup> at 100 hrs & then every 400 hrs	1 <sup>st</sup> at 100 hrs & then every 400 hrs	1 <sup>st</sup> at 100 hrs & then every 400 hrs
Service Interval Transmission	1300 hrs	1300 hrs	1300 hrs	1300 hrs

mahindra<sup>Rise</sup>

mahindra  
TRACTORS

TOUGH HARDUM

# PRESENTING THE ALL-NEW MAHINDRA TRACTORS RANGE



Max Torque  
**215 Nm**  
Backup Torque (O)  
**29.80%**

Lift Capacity  
**2000 kg**  
With Precision  
Hydraulics

Improved Operator  
Comfort &  
Convenience

GUARANTEED  
SAVINGS  
Savings Of  
1 Lakh Annually

Heavy-duty  
Build for  
Durability

**6** YEARS  
WARRANTY

Dealer's Address

Scan the QR code  
to know more




#### MAHINDRA TRACTORS

Mahindra & Mahindra Ltd., Farm Equipment Sector, Farm Division, AFS Headquarters,  
Mahindra Towers, 1st Floor, Akurli Road, Kandivali (E), Mumbai - 400101, India. Tel: 28849588, Fax: 28465813.  
☎ Toll Free No: 1800 2100 700 | <https://www.mahindractor.com> | [YouTube: https://www.youtube.com/mahindractorofficial](https://www.youtube.com/mahindractorofficial)  
📘 Facebook: <https://www.facebook.com/MahindraTractorsIndia> | [Instagram: https://www.instagram.com/mahindractorofficial](https://www.instagram.com/mahindractorofficial)  
🐦 Twitter: <https://twitter.com/TractorMahindra>



SUITED FOR EVERY TASK



**Best-in-class Torque and Power**

- Best-in-class max torque of 215 Nm
- Best-in-class backup torque (0) of 29.80%
- Strong, consistent PTO output



**Robust Transmission**

- Centre Shift (Partial Constant Mesh) and Side Shift (Full Constant Mesh)
- Operating speeds: 8F x 2R, 8F x 8R (F/R Shuttle)
- Available in single, dual & SLIPTO options



**Advanced Features**

- 2000 kg lift capacity with precision hydraulics
- SLIPTO (Independent PTO), and F/R Shuttle Variants available
- 75-lumen headlamps for working in the dark



**Durable Build**

- Heavy-Duty Front Axle for strength and stability
- Reinforced Rear Axle and Twin-Lug Wheel Rim
- Strong 3-Point Linkage with Stabilizer Bars



**Unmatched Comfort**

- New deluxe soft seat
- Convenient lever & pedal access
- 50% reduced vibrations for smoother operation



**Guaranteed Savings**

- 10% better fuel efficiency: save ₹80,000 - ₹90,000 annually
- 20% lower maintenance costs: save ₹25,000 over 2000 hours
- 6-year warranty backed by Mahindra's Trust

**PRODUCT HIGHLIGHTS**

\*Refer to the back page for exact values.

Reversible MB Plough



Rotavator



Seed Drill



Baler



Thresher



Haulage (Trolley)



Loader

