

Features	mahindra 585DI	mahindra 575DI	mahindra 575DI MS	mahindra 475DI
Engine				
Engine (CC)	2979	2979	2979	2731
No. of Cylinders	4	4	4	4
PTO power kW (HP)	36.8 (44.9)	31.1 (41.8)	29.8 (40)	27.8 (37.4)
Max Torque (Nm)	215	207	201	194
Backup Torque (%) (Declared)	21.50%	18%	20%	23%
PTO SFC (gm/hp)	190	185	185	181.9
Engine Rated RPM	2100+-(50)	2000+-(50)	2000+-(50)	2000+-(50)
Fuel Tank Capacity (litres)	50	50	48	48
Cooling System	Water Cooled / Thermostat	Water Cooled / Thermostat	Water Cooled /Thermostat	Water Cooled / Thermostat
Transmission				
Type of Transmission	PCM (CS), FCM (SS), SLIPTO	PCM (CS), FCM (SS), SLIPTO	PCM (CS), FCM (SS), SLIPTO	PCM (CS), FCM (SS), SLIPTO
Air Cleaner	Wet	Wet	Wet	Wet
Operating Speeds	8 F X 2 R, 8 F X 8 R (F/R Shuttle), 16 F X 4R (Creeper)	8 F X 2 R, 8 F X 8 R (F/R Shuttle), 16 F X 4R (Creeper)	8 F X 2 R	8 F X 2 R
Brake Type	OIB	OIB	OIB	OIB
Clutch Type	Single, Dual & SLIPTO	Single, Dual & SLIPTO	Single, Dual & SLIPTO	Single, Dual & SLIPTO
PTO Speeds	540, 540 & 540E, 540 & Reverse, 540 & 1000	540, 540 & 540E, 540 & Reverse, 540 & 1000	540, 540 & 540E, 540 & Reverse	540, 540 & 540E, 540 & Reverse
Hydraulics				
Hydraulic Lift Capacity at Hitch (Kgs)	2000	1700/2000	1700/2000	1700/2000
Hydraulic Pump Flow (Lpm)	30	28	28	28
Others				
Tyre Size Front	190.50 mm x 406.40 mm (7.5 x 16)	152.40 mm x 406.40 mm (6.0 x 16) 190.50 mm x 406.40 mm (7.5 x 16)	152.40 mm x 406.40 mm (6.0 x 16) 190.50 mm x 406.40 mm (7.5 x 16)	152.40 mm x 406.40 mm (6.0 x 16)
Tyre Size Rear	378.46 mm x 711.20 mm (14.9 x 28)	345.40 mm x 711.20 mm (13.6 x 28) 378.46 mm x 711.20 mm (14.9 x 28) (opt)	345.40 mm x 711.20 mm (13.6 x 28) 378.46 mm x 711.20 mm (14.9 x 28) (opt)	345.40 mm x 711.20 mm (13.6 x 28)
Seat	Delux	Delux	Delux	Delux
Digital Cluster & Speed Indication	Yes	Yes	Yes	Yes
Headlamp Type	Trapezoidal lamp with 75 Lux, 60-55 W	Trapezoidal lamp with 75 Lux, 60-55 W	Trapezoidal lamp with 75 Lux, 60-55 W	Trapezoidal lamp with 75 Lux, 60-55 W
SLIPTO Variant	✓	✓	✓	✓
CREEPER Variant	✓	✓	—	—
F/R Shuttle Variant	✓	✓	—	—
Service				
Service Interval Engine	1 st at 100 hrs & then every 400 hrs	1 st at 100 hrs & then every 400 hrs	1 st at 100 hrs & then every 400 hrs	1 st at 100 hrs & then every 400 hrs
Service Interval Transmission	1300 hrs	1300 hrs	1300 hrs	1300 hrs

mahindra ^{Rise}

mahindra
TRACTORS
TOUGH HARDUM

PESH HAI NAYI MAHINDRA TRACTORS RANGE

DUMDAAR POWER
ZABARDAST FEATURES



Max Torque
215 Nm
Backup Torque
21.5 %

Lift Capacity
2000 kg
With Precision
Hydraulics

Improved Operator
Comfort &
Convenience

GUARANTEED
SAVINGS
Savings Of
1 Lakh Annually

Heavy-duty
Build for
Durability

6 YEARS
WARRANTY



MAHINDRA TRACTORS

Mahindra & Mahindra Ltd., Farm Equipment Sector, Farm Division, AFS Headquarters,
Mahindra Towers, 1st Floor, Akurli Road, Kandivali (E), Mumbai - 400101, India. Tel: 28849588, Fax: 28465813.
☎ Toll Free No: 1800 2100 700 | <https://www.mahindractor.com> | 📺 YouTube: <https://www.youtube.com/mahindractorsofficial>
📘 Facebook: <https://www.facebook.com/MahindraTractorsIndia> | 📷 Instagram: <https://www.instagram.com/mahindractorsofficial>
🐦 Twitter: <https://twitter.com/TractorMahindra>

Dealer's Address





Best-in-class Torque and Power

- Best-in-class max torque of 215 Nm
- Best-in-class backup torque of 21.5%
- Strong, consistent PTO output



Robust Transmission

- Centre Shift (Partial Constant Mesh) and Side Shift (Full Constant Mesh)
- Operating speeds: 8F x 2R, 8F x 8R (F/R Shuttle), 16F x 4R (Creeper)
- Available in single, dual & SLIPTO options



Advanced Features

- 2000 kg lift capacity with precision hydraulics
- SLIPTO (Independent PTO), Creeper, and F/R Shuttle Variants available
- 75-lumen headlamps for working in the dark



Durable Build

- Heavy-Duty Front Axle for strength and stability
- Reinforced Rear Axle and Twin-Lug Wheel Rim
- Strong 3-Point Linkage with Stabilizer Bars



Unmatched Comfort

- New deluxe soft seat
- Convenient lever & pedal access
- 50% reduced vibrations for smoother operation



Guaranteed Savings

- 10% better fuel efficiency: save ₹80,000 - ₹90,000 annually
- 20% lower maintenance costs: save ₹25,000 over 2000 hours
- 6-year warranty backed by Mahindra's Trust

PRODUCT HIGHLIGHTS

*Refer to the back page for exact values.

SUITED FOR EVERY TASK



Reversible MB Plough



Rotavator



Seed Drill



Baler



Thresher



Haulage (Trolley)



Loader



475 DI 575 DI MS 585 DI 575 DI